

FPT Lubric Micro 4-20mm & FPT Lubric Pipe 25-60mm



Size	Art.Nr.	MOQ
500ml	Lubric-micro 0,5l	12pcs in box
25l	Lubric-micro 25l	-
500ml	Lubric-pipe 0,5l	12pcs in box
25l	Lubric-pipe 25l	-

A special water based lubricant for fiber optical installations. LUBRIC reduces by up to 90% of the friction generated when installing cables. Due to its consistency, fluidity and low evaporation rate, LUBRIC is recommended for all cable/pipe installations even over lengths of several kilometres without interruption (it has been used to lay cables over uninterrupted lengths of up to 6,000 m). It adheres perfectly to the cable or internal pipe surface and leaves a very tiny film. Lubric protects cables against dirt and retains its lubricating power even when water is present.

Used for installation of cables by means of the lubricated baton system, using a winch to pull the cables by controlled force. In this case, pipes need to be pre-lubricated.

Used with automatic cable insertion machines operating with compressed air. In this case, pipes need to be pre-lubricated.

Materials :

- Water emulsion of different kind of polymers

FPT Lubric Allround Gliss



Size	Art.Nr.	MOQ
1l	Lubric-gliss 1,0l	-
25l	Lubric-gliss 25l	-

Technical Specification:

- White liquid
- None odour
- Viscosity 2.000 ± 100 cps
- Mass Density 1,0 gr/cm³
- PH 7,0
- Non Inflammable
- Temperature - 5° C + 50° C
- Biodegradable
- Non-toxic

Application :

1. Shake bottle
2. Fill the dispenser
3. Or prelubricate the cable /pipe using a sponge

Suggested quantities :

- 5 ml x 1000 m for internal Ø 4 mm
- 10 ml x 1000 m for internal Ø 8 mm
- 15 ml x 1000 m for internal Ø 12 mm
- 20 ml x 1000 m for internal Ø 14 mm
- 25 ml x 1000 m for internal Ø 16 mm
- 35 ml x 1000 m for internal Ø 20 mm
- 60 ml x 1000 m for internal Ø 25-30 mm
- 70 ml x 1000 m for internal Ø 30-40 mm
- 80 ml x 1000 m for internal Ø 40-60 mm