

FIBER OPTIC CABLE BLOWING MACHINES

Technical specification



MINIFLOW (MF) PRODUCT DETAILS

USER FRIENDLY DESIGN

MiniFlow has a user friendly design, that makes for easy operation. The machine is designed with the main focus on functionality that includes:

- Rugged Stainless construction
- Safety chain guard
- Large easy to use adjustable knobs
- Push force indicator

EFFICIENT CABLE BLOWING

MiniFlow is a compact and efficient cable blowing machine. The machine is capable of installing fiber cable at a speed up to 100 m/min. and up to a distance of 3,5 km.

BUILT-IN METER COUNTER

MiniFlow has a built-in mechanical meter counter. The counter is easy to read and is robust and simple to operate. OPTIONAL: available with electronic counter and tachometer.

FLEXIBILITY

MiniFlow is very flexible, the machine can quickly be adapted to accommodate different cable and duct sizes.

CABLE DAMAGE SAFETY

MiniFlow has a unique monitoring system, which continuously monitors the pushing force, applied on the fiber cable. This makes it possible to stop the drive wheels before the cable is damaged.

The following equipment is needed to run:

- Hydraulic pump + control valve.
- High pressure compressor + hoses.

We offer all accessories on request.

Full training - theory and practice - is always provided.



Model	MiniFlow
Fiber/Cable Diameter	4-12,0 mm
Tube Size (OD)	7-20,0 mm
Product number	MF-10006
Install Speed to	100 m/min.
Distance	Up to 3.5 km
Recommended Airflow Recommended Pressure	1.000 l/pr. min. 8-16 bar air
Length: Width: Height: Weight:	650 mm 220 mm 225 mm 24kg.