

FPT Lubric Super5000 FPT Lubric Super5000Winter



Size	Art.Nr.	MOQ
250ml	Lubric-S5000	12pcs in box
250ml	Lubric-S5000Winter	12pcs in box

A special water based lubricant for fiber optical installations. LUBRIC Super 5000/5000 Winter allows to prelube the pipe or cable before/during the blowing procedure also in winter season (Super5000Winter). It adheres perfectly to the cable or internal pipe surface and leaves a very tiny film. LUBRIC Super 5000/5000 Winter protects cables against dirt and retains its lubricating power even when water is present.

LUBRIC Super 5000/5000 Winter reduces surface friction and increases the blowing distance. Due to it's consistency, fluidity and low evaporation rate, LUBRIC Super 5000/5000 Winter is recommended for all cable/pipe installations.

Application :

1. Shake bottle
2. Fill the dispenser
3. Or prelubricate the cable
/pipe using a sponge

Suggested quantities :

5 ml x 1000 m for internal Ø 4 mm
10 ml x 1000 m for internal Ø 8 mm
15 ml x 1000 m for internal Ø 12 mm
20 ml x 1000 m for internal Ø 14 mm
25 ml x 1000 m for internal Ø 16 mm
35 ml x 1000 m for internal Ø 20 mm
60 ml x 1000 m for internal Ø 25-30 mm
70 ml x 1000 m for internal Ø 30-40 mm
80 ml x 1000 m for internal Ø 40-60 mm

Materials :

- Water emulsion of different kind of polymers

Technical Specification:

- White liquid
- None odour
- Viscosity about 500 cps.
- PH 7,0
- Not flammable
- Temperature Lubric Super5000Winter : -10°C to +70° C
- Temperature Lubric Super5000 : 0°C to +70° C
- Biodegradable
- Non-toxic