

FPT Lubric Pipe 25-60mm



Size	Article Number	MOQ
500ml	70-LUBRIC/PIPE 0,5	12
25l	70-LUBRIC/PIPE 25	1

FPT Lubric Allround Gliss



Size	Article Number	MOQ
1l	70-LUBRIC/GLISS F0,5	12
25l	70-LUBRIC/GLISS F25	1

FPT Lubric Super S5000

FPT Lubric Super W5000 Winter



Size	Article Number	MOQ
500ml	70-LUBRIC S5000 0,5	15
25l	70-LUBRIC S5000 25	1
500ml	70-LUBRIC W5000 0,5	15
25l	70-LUBRIC W5000 25	1

FPT Lubric Green Water



Size	Article Number	MOQ
25l	70-Lubric Green 25	1

Lubricants

Water based

A special water based lubricant for fiber optical installations. LUBRIC allows to prelube the pipe or cable before/during the blowing procedure.

It adheres perfectly to the cable or internal pipe surface and leaves a very tiny film. Lubric protects cables against dirt and retains its lubricating power even when water is present.

LUBRIC reduces surface friction and increases the blowing distance. Due to it's consistency, fluidity and low evaporation rate, LUBRIC is recommended for all cable/pipe installations.

Materials

Water emulsion of different kind of polymers

Technical Specification:

- Green liquid
- None odour
- Viscosity 120 sec. Ford cup diam. mm 4 at 20°C
- Mass Density 1,030 (+/-) 0,03 gr/cm³
- PH 7,5 (+/-) 0,5
- Non Inflammable
- Temperature -5°C to +70°
- Temperature Lubric Super5000Winter : -10°C to +70° C
- Temperature Lubric Super5000 : 0°C to +70° C
- Biodegradable
- Non-toxic

Suggested quantities

- 5 ml x 1000 m for internal Ø 4 mm
- 10 ml x 1000 m for internal Ø 8 mm
- 15 ml x 1000 m for internal Ø 12 mm
- 20 ml x 1000 m for internal Ø 14 mm
- 25 ml x 1000 m for internal Ø 16 mm
- 35 ml x 1000 m for internal Ø 20 mm
- 60 ml x 1000 m for internal Ø 25-30 mm
- 70 ml x 1000 m for internal Ø 30-40 mm
- 80 ml x 1000 m for internal Ø 40-60 mm