

### Reducing Connector



Size(mm.)	Art.Nr.	MOQ
20-16	35-20x16	50
25-20	35-25x20	35
32-20	35-32x20	54
32-25	35-32x25	48
40-25	35-40x25	30
40-32	35-40x32	22
50-25	35-50x25	18
50-32	35-50x32	25
50-40	35-50x40	24
63-32	35-63x32	15
63-40	35-63x40	15
63-50	35-63x50	12

### Features :

- For use with HDPE pipes that comply with ISO 4427, EN 12201 and DIN 8074.
- Connects to metal and plastic accessories with ISO 7 threads.
- Made from top quality raw materials approved for drinking water by WRc, DVGW and KIWA.
- Allows easy and quick mounting without loss of parts.
- Unbreakable, corrosion-resistant and resistant to most chemicals.
- Stands up to tough working conditions, pipe bending and pulling.
- Complies with International Standards.

### Materials :

- Grip Ring- Acetal
- Nut - PPB UV stabilized with carbon black
- D-Ring - Nitril -Butyl Rubber
- Body - PPB UV stabilized with carbon black

### Performance :

- Maximum Working Temperature :  
Polypropylene 100°C  
Acetal 80°C
- Working Conditions for 50 Year Lifetime :

Working Temperature	Working Pressure
up to 23°C	16 bar
40°C	7 bar
70°C	4 bar