

**Compact Cable End Connector**


Size	Article Number	MOQ
5	28-CCEC05/0,5-2,5	25
7	28-CCEC07/1,0-3,0	25
10	28-CCEC10/2,5-4,5	25
10	28-CCEC10/3,5-6,1	25
12	28-CCEC12/2,5-4,5	25
12	28-CCEC12/3,5-6,1	25
12	28-CCEC12/6,0-8,0	25
14	28-CCEC14/4,0-8,0	25
16	28-CCEC16/4,0-8,0	25
20	28-CCEC20/4,0-8,0	25
20	28-CCEC20/6,0-10,5	25

**Seal Connector**


Size in mm	Article Number	MOQ
7/1-3,8	28-e007/GBWB1-3,8	25
8/1-2,4	28-e008/GBWB1-2,4	25
10/1-4	28-e010/GBWB1-4	25
12/3-6	28-e012/GBWB3-6	25
12/5-8	28-e012/GBWB5-8	25
14/3-6	28-e014/GBWB3-6	25
14/5-8	28-e014/GBWB5-8	25
16/5-8	28-e016/GBWB5-8	25
16/6-9	28-e016/GBWB6-9	25
20/7-10	28-e020/GBWB7-10	25
20/9-12	28-e020/GBWB9-12	25

**Materials**

- Body: PC, impact resistant
- Collet: POM, stainless steel teeth
- O-Rings: Nitrile rubber

**Performance**

- Air & Water tight: 0,5 Bar
- Insertion force: 50N max. (5 kg)

**Temperature**

- Min. working temperature: -20°C
- Max. working temperature: +60°C

**Materials**

- Body: Polycarbonate
- Guide tube retainer, release sleeve and cap: POM
- Oring seal: Nitrile
- Water block Seal: Silicone

**Performance**

- Air & Water tight: 0,5 Bar
- Peak tensile force: 200 N