

Connectors for microducts

Reducing Connector



Size in mm	Article Number	MOQ
5/3	28-PR005/003	500
6/5	28-PR006/005	260
7/4	28-PR007/004	260
7/5	28-PR007/005	260
8/3	28-PR008/003	260
8/5	28-PR008/005	260
8/7	28-PR008/007	260
10/7	28-PR010/007	140
10/8	28-PR010/008	140
12/7	28-PR012/007	120
12/8	28-PR012/008	120
12/10	28-PR012/010	120
14/10	28-PR014/010	80
14/12	28-PR014/012	80
16/10	28-PR016/010	60
16/12	28-PR016/012	60
16/14	28-PR016/014	60
20/12	28-PR020/012	15
20/14	28-PR020/014	15

Materials

- Body: PC, impact resistant
- Collet: POM, stainless steel teeth
- O-Rings: Nitrile rubber

Straight Connector



Size in mm	Article Number	MOQ
3	28-PFTC003	500
4	28-PFTC004	350
5	28-PFTC005	350
6	28-PFTC006	300
7	28-PFTC007	200
8	28-PFTC008	200
10	28-PFTC010	140
12	28-PFTC012	100
14	28-PFTC014	80
16	28-PFTC016	80
20	28-PFTC020	50

Temperature

- Min. working temperature: -20°C
- Max. working temperature: +60°C

Pressure

- Short time working pressure: 16 bar
- Insertion force: 50N max. (5 kg)

End Connector



Size in mm	Article Number	MOQ
3	28-PFTE003	600
4	28-PFTE004	600
5	28-PFTE005	600
6	28-PFTE006	500
7	28-PFTE007	400
8	28-PFTE008	400
10	28-PFTE010	300
12	28-PFTE012	200
14	28-PFTE014	180
16	28-PFTE016	120
20	28-PFTE020	100

Locking Clips



Size in mm	Article Number	MOQ
5	28-PFTL005	100
7	28-PFTL007	100
10	28-PFTL010	100
12	28-PFTL012	100
14	28-PFTL014	100
16	28-PFTL016	100
20	28-PFTL020	100